

**PRODUCT: Balmerol Licom EP 2 HT Red****1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION****PRODUCT:** BALMEROL Licom EP 2 HT Red**USE OF THE PRODUCT:** Lubricating grease**NATURE OF THE PRODUCT:** Semi solid**Supplier :** PT Balmer Lawrie Indonesia  
Grha STR 2nd floor,  
JL, Ampera Raya No. 11 Ragunan  
Pasar Minggu-Jakarta Selatan  
Indonesia**DATE OF ISSUE:** January 3rd, 2022**STATUS:** Regular

24 – Hour Health and safety emergency (Call collect) : + 62-254 402 574, + 62-254 402 579

24 – Hour Transportation emergency:, + 62-254 402 574, + 62-254 402 579

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

Ingredients present at or above 0.1 wt % (classified as toxic or very toxic) or 1 wt % (classified as harmful, irritant or corrosive).

**HAZARDOUS INGREDIENT:**

APPROXIMATE CONCENTRATION None See section 8 for exposure limits ( if applicable)

The chemical identity of some or all of the ingredients is confidential business information and is being withheld. In the event of a medical emergency, compositional information will be provided to medical staff.

**3. HAZARD IDENTIFICATION**

Under normal conditions of use, this product is not considered hazardous according to regulatory guidelines. (See section 15)

It is of low oral and dermal toxicity and under normal conditions of use should present no significant health hazards. Handling precautions should be strictly observed.

**4. FIRST AID****INHALATION:** Remove from further exposure. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with mechanical device or use mouth-to-mouth resuscitation.**SKIN CONTACT:** Wash contact areas with soap and water. Remove and clean the grease soaked clothing and wash affected area.**EYE CONTACT:** Rinse immediately with plenty of water until irritation subsides. If irritation persists, obtain medical advice.**INJECTION INJURY WARNING:** if the product is injected into or under the skin or into any part of the body, regardless of the appearance of the wound or its size, a physician as a surgical emergency should evaluate the individual immediately.

Even though initial symptoms from high-pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

**PRODUCT: Balmerol Licom EP 2 HT Red****5. FIRE-FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Carbon dioxide, foam, dry chemical and water fog.

**FIRE AND EXPLOSION HAZARDS:** Combustible material, low hazard. The product can form flammable mixtures or can burn only on heating above the flash point. However, minor contamination by hydrocarbons of higher volatility may increase the hazard.

**SPECIAL FIRE FIGHTING PROCEDURES:** Water or foam may cause frothing. Use water to keep fire exposed containers cool. Water spray may be used to flush spills away from exposure. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

**SPECIAL PROTECTIVE EQUIPMENT:** For fires in enclosed areas, fire fighters must use self-contained breathing apparatus.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** None.

**COMBUSTION PRODUCTS:** Smoke and carbon monoxide may be formed in the event of incomplete combustion.

Flash Point C(F): > 260(500) (Estimated for the oil, ASTM D-92 (COC)).

Flammable Limits (approx.% vol.in air) - LEL: NE, UEL: NE

**NFPA HAZARD ID:** Health: 0, Flammability: 1, Reactivity: 0

**6. ACCIDENTAL RELEASE MEASURES**

**NOTIFICATION PROCEDURES:** Report spills/ releases as required appropriating authorities.

**PROCEDURES IF MATERIAL IS RELEASED OR SPILLED:**

**LAND SPILL:** Shut off source taking normal safety precautions. Take measures to minimize the effects on ground water. Recover by pumping or contain spilled material with sand or other suitable absorbent and remove mechanically into containers. If necessary, dispose of adsorbed residues as directed in Section 13.

**WATER SPILL:** Confine the spill immediately with brooms. Warn other ships in the vicinity. Notify port and other relevant authorities. Remove from the surface by skimming or with suitable absorbents. If permitted by regulatory authorities the use of suitable dispersants should be considered where recommended in local oil spill procedures.

**ENVIRONMENTAL PRECAUTIONS:** Prevent material from entering sewers, water sources or low lying areas; advise the relevant authorities if it has, or if it contaminates soil/vegetation.

**PERSONAL PRECAUTIONS:** See Section 8

**7. HANDLING AND STORAGE**

**PRECAUTIONARY MEASURES:** Keep out of reach of children.

**HANDLING:** High-pressure injection under the skin may occur due to the rupture of pressurized lines. Always seek medical attention. No special precautions are necessary beyond normal good hygiene practices. See Section 8 for additional personal protection advice when handling this product.

**STORAGE:** Keep containers closed when not in use. Store away from strong oxidizing agents and combustible materials. Do not store near heat, sparks, flame or strong oxidants.

**SPECIAL PRECAUTIONS:** Prevent small spills and leakages to avoid slip hazard.

**EMPTY CONTAINER WARNING:** Empty containers retain residue (liquid and/or vapor) and can be dangerous.

**DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.** Do not attempt to refill or clean container since residue is difficult to remove.

Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

**PRODUCT: Balmerol Licom EP 2 HT Red****8. EXPOSURE CONTROLS AND PERSONAL PROTECTION**

**OCCUPATIONAL EXPOSURE LIMITS:** This product does not contain any components, which have recognized exposure limits.

**VENTILATION:** Use adequate ventilation.

**RESPIRATORY PROTECTION:** No special requirements under ordinary conditions of use and with adequate ventilation.

**EYE PROTECTION:** Generally eye contact is unlikely with this type material. If eye contact is likely, safety glasses with side shields or chemical type goggles should be worn.

**SKIN PROTECTION:** If prolonged or repeated skin contact is likely, oil impervious gloves should be worn. Good personal hygiene practices should always be followed.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Typical physical properties are given below. Consult Product Data Sheet for specific details.

**APPEARANCE:** Semisolid mass.

**COLOR:** Red

**ODOR:** Mild

**ODOR THRESHOLD-ppm:** NE

**pH:** NA

**BOILING POINT C(F):** > 316(600)

**DROP POINT C(F):** > 300 (572)

**FLASH POINT C(F):** > 260(500) (Estimated for oil, ASTM D-92 (COC))

**FLAMMABILITY (solids):** NE

**AUTO FLAMMABILITY C(F):** NA

**EXPLOSIVE PROPERTIES:** NA

**OXIDIZING PROPERTIES:** NA

**VAPOR PRESSURE-mmHg 20 C:** < 0.1

**VAPOR DENSITY:** NE

**EVAPORATION RATE:** NE

**RELATIVE DENSITY, 15/4 C:** approx. 0.900

**SOLUBILITY IN WATER:** Negligible

**PARTITION COEFFICIENT:** > 3.5

**VISCOSITY AT 40 C, cSt:** 220 min

**VISCOSITY AT 100 C, cSt:** 15 min

**POUR POINT C(F):** NA

**FREEZING POINT C(F):** NE

**VOC:** < 1.00 (Wt. %); 0.083 lbs/gal

**NOTE:** MOST PHYSICAL PROPERTIES FOR OIL COMPONENT.

DMSO EXTRACT, IP-346 (WT.%): <3, for mineral oil only

NA=NOT APPLICABLE NE=NOT ESTABLISHED D=DECOMPOSES

FOR FURTHER TECHNICAL INFORMATION, CONTACT OUR MARKETING REPRESENTATIVE

**10. STABILITY AND REACTIVITY**

**STABILITY (THERMAL, LIGHT, ETC.):** Stable.

**CONDITIONS TO AVOID:** Extreme heat and high-energy sources of ignition.

**INCOMPATIBILITY (MATERIALS TO AVOID):** Strong oxidizers.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Product does not decompose at ambient temperatures.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**PRODUCT: Balmerol Licom EP 2 HT Red****11. TOXICOLOGICAL INFORMATION****ACUTE TOXICOLOGY**

**ORAL TOXICITY (RATS):** Practically non-toxic (LD50: greater than 5000 mg/kg). ---Based on testing of similar products and/or the components.

**DERMAL TOXICITY (RABBITS):** Practically non-toxic (LD50: greater than 5000 mg/kg). ---Based on testing of similar products and/or the components.

**INHALATION TOXICITY (RATS):** Practically non-toxic (LC50: greater than 5 mg / l). ---Based on testing of similar products and/or the components.

**EYE IRRITATION (RABBITS):** Practically non-irritating. (Draize score: greater than 6 but 15 or less)-Based on testing of similar products and/or the components.

**SKIN IRRITATION (RABBITS):** Practically non-irritating. (Primary Irritation Index: greater than 0.5 but less than 3) - Based on testing of similar products and/or the components.

**OTHER ACUTE TOXICITY DATA:** Although an acute inhalation study was not performed with this product, a variety of mineral oils and synthetic base oils, such as those in this product have been tested. These samples had virtually no effect other than a nonspecific inflammatory response in the lung to the aerosolized mineral oil. The presence of additives in other tested formulations (in approximately the same amounts as in the present formulation) did not alter the observed effects.

**SUBCHRONIC TOXICOLOGY (SUMMARY)** No significant adverse effects were found in studies using repeated dermal applications of similar formulations to the skin of laboratory animals for 13 weeks at doses significantly higher than those expected during normal industrial exposure. The animals were evaluated extensively for effects of exposure (hematology, serum chemistry, urinalysis, organ weights, microscopic examination of tissues etc.).

**REPRODUCTIVE TOXICOLOGY (SUMMARY)** No Teratogenicity effects would be expected from dermal exposure, based on laboratory developmental toxicity studies of major components in this formulation and/or materials of similar composition.

**CHRONIC TOXICOLOGY (SUMMARY)** Repeated and/or prolonged exposure may cause irritation to the skin, eyes or respiratory tract. For mineral base oils: Base oils in this product are severely solvent refined and/or severely hydro treated. Chronic mouse skin painting studies of severely treated oils showed no evidence of carcinogenic effects. These results are confirmed on a continuing basis using various screening methods such as Modified Ames Test, IP-346, and/or other analytical methods. For synthetic base oils:

**SENSITIZATION (SUMMARY)** not expected to be sensitizing based on tests of this product, components, or similar products.

**12. ECOLOGICAL INFORMATION**

This environmental assessment was conducted using information on the individual components, as no test data was available for this specific formulation.

**ECOTOXICITY:** The major components in the formulation show no aquatic toxicity at 1000 mg/L loading; therefore long-term adverse effects in the aquatic environment are not expected.

**MOBILITY:** Not established.

**PERSISTENCE AND DEGRADABILITY:** This product is expected to be inherently biodegradable, as the principal components have been shown to degrade at slow to moderate rates.

**BIOACCUMULATIVE POTENTIAL:** Not established.

**13. DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL:** Product is suitable for burning in an enclosed, controlled burner for fuel value. Such burning may be limited pursuant to the Resource Conservation and Recovery Act. In addition, the product is suitable for processing by an approved recycling facility or can be disposed of at an appropriate government waste disposal facility. Use of these methods is subject to user compliance with applicable laws and regulations and consideration of product characteristics at time of disposal.

**RCRA INFORMATION:** The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste (40 CFR, Part 261D), nor is it formulated to contain materials which are listed hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, or reactivity. The unused product is not formulated with substances covered by the Toxicity Characteristic Leaching procedure (TCLP). However, used product may be regulated.

**PRODUCT: Balmerol Licom EP 2 HT Red**

**14. TRANSPORT INFORMATION**

**USUAL SHIPPING CONTAINERS:** Rail cars, tank trucks, drums.  
**USA DOT:** NOT REGULATED BY USA DOT.  
**RID/ADR:** NOT REGULATED BY RID/ADR.  
**IMO:** NOT REGULATED BY IMO.  
**IATA:** NOT REGULATED BY IATA.

**15. REGULATORY INFORMATION**

**OSHA HAZARD COMMUNICATION STANDARD:** When used for its intended purposes, this product is not classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

**EU Labelling:** Product is not dangerous as defined by the European Union Dangerous Substances/ Preparations Directives. EU labelling not required.

**Governmental Inventory Status:** All components comply with TSCA, EINECS/ELINCS and AICS. U.S. Superfund Amendments and Reauthorization Act (SARA) Title III ; This product contains no "EXTREMELY HAZARDOUS SUBSTANCES".

**SARA (311/312) REPORTABLE HAZARD CATEGORIES:** None.

This product contains the following SARA (313) Toxic Release Chemicals:  
 CHEMICAL NAME CAS NUMBER CONC.

Substance/Chemical identity	EC Classification	CAS-No.	Conc.( %)
1. Refined mineral base Oils	N/C	64741 – 88 - 4	83.75 – 87.75
	N/C	64741 – 89 - 5	
	N/C	64741 – 96 - 4	
	N/C	64741 - 97 - 5	
	N/C	64742 – 01 - 4	
	N/C	64742 – 52 - 5	
	N/C	64742 – 53 - 6	
	N/C	64742 – 54 - 7	
	N/C	64742 – 62 - 7	
	N/C	64742 – 65 - 0	
N/C	64743 – 83 - 7		
2. Lithium complex soap thickener	N/C	7620 – 77 - 1	10 - 12
3. Lithium Hydroxide Monohydrate	R 43	1310 – 66 - 3	0.05 max
4. Antioxidant	R 36 / 38	26523 – 78 - 4	0.50 max
5. Antirust	N/C	Proprietary	0.50 max
6. EP additive	N/C	Proprietary	1 - 3
7. Red dye	N/C	Proprietary	0.10 max
8. Tackifier	N/C	Proprietary	0.10 max

**REGULATORY LISTS SEARCHED**

1=ACGIH ALL 6=IARC 1 11=TSCA 4 16=CA P65 CARC 21=LA RTK  
 2=ACGIH A1 7=IARC 2A 12=TSCA 5a2 17=CA P65 REPRO 22=MI 2933=ACGIH A2 8=IARC 2B 13=TSCA 5e  
 18=CA RTK 23=MN RTK  
 4=NTP CARC 9=OSHA CARC 14=TSCA 6 19=FL RTK 24=NJ RTK  
 5=NTP SUS 10=OSHA Z 15=TSCA 12b 20=IL RTK 25=PA RTK  
 26=RI RTK

**PRODUCT: Balmerol Licom EP 2 HT Red****16. OTHER INFORMATION****USE:**

**AUTOMOTIVE USE:** Health studies have shown that many hydrocarbons pose potential human health risks, which may vary from person to person. Information provided on this MSDS reflects intended use. This product should not be used for other applications. In any case, the following advice should be considered:

**INDUSTRIAL USE:** Under normal conditions of intended use, this product does not pose a risk to health. Excessive exposure may result in eye, skin or respiratory irritation. Always observe good hygiene measures.

**FIRST AID:** Wash skin with soap and water. Flush eyes with water. If overcome by fumes or vapor, remove to fresh air. If ingested do not induce vomiting. If symptoms persist seek medical assistance. Read and understand the MSDS before using this product. Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control; all risks of use of the product are therefore assumed by the user and WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO THE USE OR SUITABILITY OF THE PRODUCT. Nothing is intended as a recommendation for uses, which infringe valid patents, or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted.